

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Contract Group 12

Scope: Resilient, textile and laminate floor coverings for interior use

The product fulfils the essential characteristic of **reaction to fire**:

Class C_{fl}-s1.

Intended use: Flooring

Placed on the market under the name or trade mark of:
Bentzon Carpets ApS
Fabrikvej 15
Middelfart 5500

and produced in the manufacturing plant:
CPA20011/CPA20017

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

EN 14041:2004 : **Resilient, textile and laminate floor coverings - Essential characteristics**
EN 14041:2004/AC:2006

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: **2021-01-18.**

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate issued 2019-11-27)

This certificate was first issued 2014-07-24.



Thomas Anthony Wilson
Responsible for evaluation



Merete Poulsen
Responsible for certification decision

The certificate shall be reproduced in extenso
– extracts only with written permission from DBI Certification A/S.

Annex 1

EXTENT

Type	Description
<p>Sigma Zeta Cable Canvas Herring Rib</p> <p>Field of application</p>	<p>Tufted carpet with cut loop pile.</p> <p>Pile: 100 % Polyamid, 500 g/m²</p> <p>Rear side: textile</p> <p>Total height: approx. 3 to 3.5 mm</p> <p>Pile height: approx. 1.5 to 2 mm mm</p> <p>Total weight:1600 to 2200 g/m²</p> <p>The carpet is to be mounted on a substrate of classes A1 or A2-s1,d0 at least 6 mm thick and with density equal to or greater than 1200 kg/m³ with a polyacrylat-copolymer dispersion adhesive, application rate: 300-350 g/m² (wet).</p>

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.

Annex 2

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
DBI	PFA10561a	2014-06-02
DBI	PFA10561b	2014-06-03
DBI	PFA11436A	2019-10-30
DBI	PCA10139rev3	2019-10-30

Annex 3

TECHNICAL BASIS

Designation	Identification	Date
Product specification	VH09042014.1	2014-07-24
Product specification	VH12032014.1	2014-07-24
Product specification	V09102019.1	2019-10-09
Product specification	VH23102020.1	2020-10-23
Product specification	VH23102020.1	2020-10-23
Product specification	VH23102020.1	2020-10-23

The certificate shall be reproduced in extenso
 – extracts only with written permission from DBI Certification A/S.