

**CERTIFICATE OF CONSTANCY OF PERFORMANCE**

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Contract Group 7**

Scope: Resilient, textile and laminate floor coverings for interior use

The product fulfils the essential characteristic of **reaction to fire**:

**Class C<sub>fl</sub>-s1.**

Intended use: Flooring

Placed on the market under the name or trade mark of:  
**Bentzon Carpets ApS**  
**Fabrikvej 15**  
**Middelfart 5500**

and produced in the manufacturing plant:  
**CPA20011**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

**EN 14041:2004/AC:2006** : **Resilient, textile and laminate floor coverings - Essential characteristics**

under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

The attached annexes form part of this certificate.

Date of issue: **2020-05-28**.

This certificate will remain valid as long as neither the harmonized standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly unless suspended or withdrawn by the notified product certification body.

(This certificate supersedes the previous version of this certificate issued 2016-06-01)

This certificate was first issued 2016-05-23.



Thomas Anthony Wilson  
Responsible for evaluation



Merete Poulsen  
Responsible for certification decision

Annex 1

The certificate shall be reproduced in extenso  
– extracts only with written permission from DBI Certification A/S.

**EXTENT**

Type	Description
Alfa Textile	Woven Contract Bouclé carpet
Beta Textile	Pile: 100% Polyamide, 700-750, g/m <sup>2</sup>
Beta Design Textile	Rear side: woven textile
Gamma Textile	Total height: 4-4,5 mm Pile height: 2 mm Total weight: 2100- 2400 g/m <sup>2</sup>
Field of application	The carpet is to be mounted on a substrate of classes A1 or A2-s1,d0 at least 6 mm thick and with density equal to or greater than 1200 kg/m <sup>3</sup> with a polyacrylat-copolymer dispersion adhesive, application rate: 300-350 g/m <sup>2</sup>

The certificate shall be reproduced in extenso  
 – extracts only with written permission from DBI Certification A/S.

Annex 2

**TEST DOCUMENTATION**

Accredited Laboratory	Report no.	Date
DBI	PFA10856A	2016-04-26
DBI	PFA10856B	2016-04-26
DBI	PCA10355A	2016-04-26

Annex 3

**TECHNICAL BASIS**

Designation	Identification	Date
Product specification		
Alfa Textile	V12062015.1	2015-06-12
Beta Textile	V12062015.1	2015-06-12
Beta Design Textile	V12062015.1	2015-06-12
Gamma Textile	V12062015.1	2015-06-12
Supplementary information	Backing information	2014-03-25

The certificate shall be reproduced in extenso  
 – extracts only with written permission from DBI Certification A/S.